

OFFICE OF NAVAL RESEARCH

Contract N00014-90-J-1193

TECHNICAL REPORT No. 2

New Type of Optical Bistability in Polymers Mediated by Phonons

by

Xiao-shen Li, D. L. Lin, Thomas F. George and Xin Sun

Prepared for Publication

in


Physical Review B

Departments of Chemistry and Physics State University of New York at Buffalo Buffalo, New York 14260

December 1989

Reproduction in whole or in part is permitted for any purpose of the United States Government.

This document has been approved for public release and sale; its distribution is unlimited.



ECURITY	CLASSIFIC	ATION OF	THIS PAGE

REPORT DOCUMENTATION PAGE						
1a. REPORT SECURITY CLASSIFICATION Unclassified			1b. RESTRICTIVE MARKINGS			
2b. DECLASSIFICATION/DOWNGRADING SCHEDULE			lease;	distribution unlimited		
	5. MONITORING	ORGANIZATION RE	PORT NU	MBER(S)		
YMBOL	7a. NAME OF MO	ONITORING ORGAN	IZATION			
able)						
			ode)			
	9. PROCUREMEN	T INSTRUMENT IDE	NTIFICAT	TION NUMBER		
	Contract	N00014-90-J-	-1193			
	10 SOURCE OF	LINDING NILIMBERS				
ļ.				WORK UNIT		
	ELEMENT NO.	NO.	NO.	ACCESSION NO.		
				1		
						
Polyme	rs Mediated	by Phonons				
Thoma	s F. George	and Xin Sun				
	14. DATE OF REPORT (Year, Month, Day) 15. PAGE COUNT					
	Gula in					
Physica	l Review B					
TERMS (ontinue on revers			by block number)		
	TT TIPY ()	NEW T				
19. ABSTRACT (Continue on reverse if necessary and identify by block number)						
y block ne	imber)					
lity me	diated by ph	ionon and vir	tual	exciton		
Nume	rical result	s with param	eters	pertaining		
e are	given as an	illustration	. The	e stability		
mined,	and the phy	sical mechan	ism re	esponsibl e		
r	. •					
	21. ABSTRACT SE	CURITY OF ASSISTA	TION			
IC USERS						
			22c. O	FFICE SYMBOL		
	(MBOL ble) Polyme Thoma Terms (C BISTAB BY PH y block not ity me Nume e are mined,	1b. RESTRICTIVE 3. DISTRIBUTION Approved for State of the state of th	3. DISTRIBUTION / AVAILABILITY OF Approved for public rel 5. MONITORING ORGANIZATION RE 7b. ADDRESS (City, State, and ZIPC Chemistry Program 800 N. Quincy Street Arlington, Virginia 200 N. Quincy Street Arlington, No. 200 N. Quincy Street Arlington, N	3. DISTRIBUTION/AVAILABILITY OF REPORT Approved for public release; 5. MONITORING ORGANIZATION REPORT NUMBER 7. NAME OF MONITORING ORGANIZATION REPORT NUMBERS (City, State, and ZIP Code) Chemistry Program 800 N. Quincy Street Arlington, Virginia 22217 (MBOL) Contract N00014-90-J-1193 10. SOURCE OF FUNDING NUMBERS PROGRAM ELEMENT NO. PROJECT NO. TASK NO. Polymers Mediated by Phonons Thomas F. George and Xin Sun 14. DATE OF REPORT (Year, Month, Day) December 1989 hysical Review B TERMS (Continue on reverse if necessary and identify NEW TYPE BISTABILITY VIRTUAL EX BY PHONONS THEORY y block number) ity mediated by phonon and virtual Numerical results with parameters e are given as an illustration. The mined, and the physical mechanism relation, and the physical mechanism relation, and the physical mechanism relation. The mined, and the physical mechanism relation.		

DD Form 1473, JUN 86

Previous editions are obsolete.

SECURITY CLASSIFICATION OF THIS PAGE

Physical Review B, in press

New type of optical bistability in polymers mediated by phonons

Xiao-shen Li*, D. L. Lin and Thomas F. George
Department of Physics and Astronomy
239 Fronczak Hall
State University of New York at Buffalo
Buffalo, New York 14260

Xin Sun
Center of Theoretical Physics
Chinese Center of Advanced Science and Technology (World Laboratory)
Beijing 100080

and


Department of Physics Fudan University Shanghai 100433, People's Republic of China

Abstract

A new type of optical bistability mediated by phonon and virtual exciton coupling is suggested for polymers. Numerical results with parameters pertaining to polydiacetylene-toluene-sulfonate are given as an illustration. The stability of the steady-state solution is examined, and the physical mechanism responsible for the bistability is discussed.

1988 PACS numbers: 42.65.-k, 42.65.pc, 36.20.-r, 78.65.Hc

* On leave of absence from the Shanghai Institute of Metallurgy, Academia Sinica, Shanghai, People's Republic of China.



In the transparent region well below the absorption edge of semiconductor quantum wells, a considerable amount of work has been done on nonlinear coherent optical processes due to the excitation of light. 1-4 Such investigations have been extended to polymers in recent years. 5-8 When the frequency of the incident laser beam is tuned below the exciton resonance in the semiconductor, it is known that virtual excitons are generated. These excitons interact nonlinearly with photons in the same way as real excitons. 2,4-6 This nonlinear interaction, sometimes known as the phase space filling effect, determines the spectral changes associated with the optical excitation of two-dimensional (2D) systems of semiconductor quantum wells or of one-dimensional (1D) systems of polymers. It also predicts a reduction in exciton oscillator strength or a bleaching of the exciton transition.

Several recent studies $^{6-8}$ have demonstrated that it is the optical phonon modes that mediate the exciton bleaching in volydiacetylene-toluene sulfonate (PTS). Conjugated polymers have attracted much attention because of their large nonlinear optical susceptibility $\chi^{(3)}$. All these point to their tremendous potential of applications in optical signal processing and high-speed computing. It is therefore of great interest to investigate the fundamental medianism that yields such a giant optical nonlinearity.

We consider a this Communication the special case in which a sample of polymer is contained in an optical cavity, and study its response to a laser beam directed into the cavity. The polymer system in our treatment is described by a Hamiltonian which is obtained by adding the photon-exciton interaction to the model proposed in Ref. 6. This simple model has been proven successful in the explanation of phonon-mediated optical Stark effect observed experimentally. The purpose of this paper is to investigate the relation between the input optical field intensity and the output intensity

with special interest in the possible existence of any optical multistability in the system. Our approach is semiclassical in the sense that quantum fluctuations are neglected as usual. The phonon and exciton variables are then eliminated adiabatically in our search for the multistability.

The total Hamiltonian can be written as

$$H = \Omega a^{\dagger} a + \omega_{ph} b^{\dagger} b + \omega_{ex} c^{\dagger} c + \lambda c^{\dagger} c (b + b^{\dagger})$$

$$+ ig(a^{\dagger} c - c^{\dagger} a) + i(a^{\dagger} E e^{-i\Omega t} - aE * e^{i\Omega t}) , \qquad (1)$$

where we have ignored the spatial variation of the cavity field which creates the virtual exciton. We consider in (1) only one of the many phonon modes coupling most strongly to the exciton and neglect the momentum dependence of the exciton. Here, $a^{\dagger}(a)$, $b^{\dagger}(b)$ and $c^{\dagger}(c)$ are the creation (annihilation) operators for the cavity field, phonon and exciton, respectively, with corresponding frequencies Ω , $\omega_{\rm ph}$ and $\omega_{\rm ex}$. λ is the coupling constant for the phonon-exciton interaction, while g stands for the exciton-field coupling constant. The coherent driving field is taken to have the same frequency Ω , and its amplitude is E.

As mentioned above, our approach is semiclassical. The procedure is as follows. We first find from the Hamiltonian (1) equations of motion for the operators a, b, c in the rotating frame. Then we replace the operators by their mean values defined as classical variables α = <a>, β = , η = <c> and η_c = <c † c>. In other words, in the limit of zero fluctuations, all correlation functions may factorize and we have the optical Bloch-like equations

$$\dot{\alpha} = E - \kappa \alpha + g \eta \tag{2a}$$

$$\dot{\beta} = -(i\omega_{\rm ph} + \gamma_{\rm ph})\beta - i\lambda n_{\rm c}$$
 (2b)

$$\dot{\eta} = -(i\Delta + \gamma_{ex})\eta - i\lambda\eta(\beta + \beta^*) - g\alpha$$
 (2c)

$$\dot{n}_{c} = -g(\alpha * \eta + \eta * \alpha) - \gamma_{ex} n_{c} , \qquad (2d)$$

where we have defined the detuning $\Delta = \omega_{\rm ex} - \Omega$. The damping rates κ , pn and $\gamma_{\rm ex}$ have been introduced phenomenologically.

In the limit of high Q cavity, we have $\kappa << \gamma_{\rm ex}, \gamma_{\rm ph}$. Consequently, the excitonic and phononic variables can be eliminated adiabatically. In other words, the time variation of these variables are assumed to follow that of the fields. By setting the left-hand side equal to zero, it is therefore straightforward to obtain from Eqs. (2b)-(2d)

$$\beta = -\lambda(\omega_{\rm ph} + i\gamma_{\rm ph})n_{\rm c}/(\omega_{\rm ph}^2 + \gamma_{\rm ph}^2)$$
 (3a)

$$\beta + \beta \star \approx -2\lambda n_{c}/\omega_{ph}$$
 (3b)

$$\eta = -g(1 - i\gamma)\alpha/(1 + Y^2)$$
 (3c)

$$\lambda_{\rm p}^2 n_{\rm c}^3 - 2\lambda_{\rm p} \Delta n_{\rm c}^2 + (1 + \Delta^2) n_{\rm c} - 2g^2 |\alpha|^2$$
, (3d)

where we have defined

$$Y = \Delta - \lambda_{p} r_{c} \tag{4a}$$

$$\lambda_{\rm p} = 2\lambda^2/\omega_{\rm ph} \tag{4b}$$

and have made use of the fact that $\omega_{\rm ph} >> \gamma_{\rm ph}$. All quantitites with the dimension t⁻¹ are measured in the unit $\gamma_{\rm ex} = 1$. Equation (3c) follows directly from (2c) and 3(b), and (3d) is obtained by plugging (3c) in (2d).

For convenience, we now introduce the dimensionless variables $r=\kappa t$, $E=E/\kappa$ and $\alpha_{\rm C}=\sqrt{2\,{\rm g}^2}\alpha$. The equation of motion (2a) for the field mode then becomes

$$\frac{\partial}{\partial \tau} \alpha_{c} = \sqrt{2g^{2}} E - \alpha_{c} f(|\alpha_{c}|^{2}) , \qquad (5)$$

where the function f is defined as

$$f(|\alpha_c|^2) = 1 + (\frac{g^2}{\kappa}) \frac{1 - i[\Delta - \lambda_p n_c(|\alpha_c|^2)]}{1 + [\Delta - \lambda_p n_c(|\alpha_c|^2)]^2}.$$
 (6)

That the number of virtual excitons n_c is a function of the field intensity I = $|\alpha_c|^2$ only is clearly seen from (3d). In the steady state, we set $\alpha_c = \alpha_s = constant$ in (5) and (6). A straightforward calculation then leads to

$$I_{s} = \frac{1 + Y_{s}^{2}(I_{in})}{(1 + g^{2}/\kappa)^{2} + Y_{s}^{2}(I_{in})} I_{in} , \qquad (7)$$

where we have defined the steady-state cavity field intensity $I_s = |\alpha_s|^2$, the driving field intensity $I_{in} = 2g^2|E|^2$ and $Y_s(I_{in}) = \Delta - \lambda_p n_s(I_{in})$. The fact that n_s is a function of the driving field intensity I_{in} is seen from

$$n_s^3 - 2(\Delta/\lambda_p)n_s^2 + [\Delta^2 + (1 + g^2/\kappa)^2]\lambda_p^{-2}n_s - I_{in}/\lambda_p^2 = 0$$
, (8)

which follows from (3d) and (7). Equation (8) may have one or three real roots depending on the parameters chosen. If there are three possible values of n_s for a given I_{in} , Eq. (7) implies that there may exist three possible intensities of the output light since the output intensity is proportional to the cavity field intensity.

It is necessary to determine the stability of the steady-state solutions. This may be done in a similar fashion as discussed in Ref. 11. Consider a general differential equation of the type

$$\dot{\alpha}_{c} = F(\alpha_{c}, \alpha_{c}^{\star}) \quad , \tag{9}$$

which may be linearized by a standard procedure for small perturbations $\delta\alpha_{\rm C}$ and $\delta\alpha_{\rm C}^{\star}$ about their steady-state solutions $\alpha_{\rm S}$ and $\alpha_{\rm S}^{\star}$. The resulting linear equation is

$$\frac{\partial}{\partial r} \begin{pmatrix} \delta \alpha_{\rm c} \\ \delta \alpha_{\rm c}^* \end{pmatrix} = A \begin{pmatrix} \delta \alpha_{\rm c} \\ \delta \alpha_{\rm c}^* \end{pmatrix} , \qquad (10)$$

where the matrix A is given by

$$A = \begin{bmatrix} \frac{\partial}{\partial \alpha_{c}} & F(\alpha_{s}, \alpha_{s}^{*}) & \frac{\partial}{\partial \alpha_{c}^{*}} & F(\alpha_{s}, \alpha_{s}^{*}) \\ & & & \\ \frac{\partial}{\partial \alpha_{c}} & F^{*}(\alpha_{s}, \alpha_{s}^{*}) & \frac{\partial}{\partial \alpha_{c}^{*}} & F^{*}(\alpha_{s}, \alpha_{s}^{*}) \end{bmatrix}$$
(11)

The condition for stability is that the eigenvalues of A must have negative real parts, which requires that Tr|A| < 0 and det|A| > 0. More explicitly, we have

$$\frac{\partial}{\partial \mathbf{u}} (\text{ReF}) + \frac{\partial}{\partial \mathbf{v}} (\text{ImF}) < 0$$
 (12a)

$$\frac{\partial}{\partial u}$$
 (ReF) $\frac{\partial}{\partial v}$ (ImF) - $\frac{\partial}{\partial v}$ (ReF) $\frac{\partial}{\partial u}$ (ImF) > 0 , (12b)

where $u = Re(\alpha_c)$ and $v = Im(\alpha_c)$. Thus the stability conditions for our Eq. (5) are

$$f_1(I_s) + I_s \frac{\partial}{\partial I} f_1(I_s) > 0$$
 (13a)

$$\sum_{i=1}^{2} f_{i}(I_{s})[f_{i}(I_{s}) + 2I_{s} \frac{\partial}{\partial I} f_{i}(I_{s})] > 0 , \qquad (13b)$$

where $f_1(f_2)$ is the real (imaginary) part of f.

On the other hand, since Eq. (8) has only one real root for $\Delta \leq 0$, it is quite clear that there is no multiple output intensity whenever the cavity field is tuned on or above the resonance with the exciton, no matter how strong the input intensity is. The situation is the same when no phonons are involved or when $\lambda_p = 0$. Therefore, the presence of the optical multistability is really mediated by the phonons via their nonlinear interaction with virtual excitons.

It is known that polydiacetylenes possess not only large $\chi^{(3)}$ but also small transmission loss α . An added attraction is their flexibility in the

construction of waveguides. 11 We consider in what follows polydiacetylenetoluene-sulfonate (PTS) as a specific example in our numerical calculation. Following Ref. 6, we take only one of the phonon modes which couple most strongly to the excitons. The parameters for PTS are 6,7 $\gamma_{\rm ex} = 0.05$ eV, $\omega_{\rm nh} =$ 0.258 eV, λ = 0.1 eV and $\gamma_{\rm ph}$ = 0.002 eV. The steady-state intensity I has been calculated numerically as a function of I_{in} with the energy unit γ_{ex} . Thus $\omega_{\rm ph} = 5.16$ and $\lambda = 2.0$. The results for different values of Δ and ${\rm g}^2/{\rm g}$ are plotted in Fig. 1. It is found that only when the cavity field is tuned sufficiently below the exciton resonance, say by an amount $\geq \frac{1}{2} \omega_{\rm ph}$, does there exist optical tristability. When the cavity damping is large or when g^2/κ is small, there is no such nonlinear phenomenon either. This means that the cavity feedback is one of the vital factors to creat optical tristability in the present case. On the other hand, such nonlinear phenomenon does not appear in cavities of very high quality, namely, cavities of exceedingly high figure of merit Q, or g^2/κ is large. This implies that enough line width of the cavity is required to create such nonlinear interactions, and hence that this tristability is at least a dispersive one.

Through the linearized stability analysis of the steady-state solutions discussed above, we have found that all the multiple solutions are stable except for those in the vicinity of turning points such as A and B in Fig. 1 (b) and (c). Hence, when the input field intensity increases continuously, passing the turning point, and then decreases, the output field intensity will follow a reversed hysteresis loop. In contrast to the ordinary optical bistability behavior, this novel multistability behaves more like the special hysteresis loop in systems that exhibit increasing absorption optical bistability. ¹³ It is also of interest to note that the middle branch as well as the other two as shown in the figure is stable. This is of course very

different from what happens in ordinary cases. However, as long as the input field intensity manges monotonically, the cavity field intensity is not expected to move into the middle branch. For instance, the system follows the upper branch as I_{in} increases until it reaches the turning point A where it is unstable and jumps to the lower branch as I_{in} increases further. Similarly, the system follows the lower branch and jumps to the upper branch at the unstable point B when I_{in} decreases. It is not impossible to reach the middle branch if the input intensity reverses its course of change at the turning points. In addition, we learn from the numerical study that the threshold for the bistability is raised by increasing the detuning Δ . Thus, a proper choice of Δ may be preferable for the realization of optical bistability.

We now attempt to understand physically the mechanism responsible for this novel phenomenon of reversed optical bistability. It is seen from Eq. (3c) that the resonance enhancement of the dipole moment in steady state occurs at ω_{x} - Ω - λ_{p} n = 0. The term λ_{p} n may be regarded as the lattice relaxation energy. 6 Therefore both the real and imaginary parts of the optical response of the PTS system depend upon this relaxation energy, which is directly proportional to the number of virtual excitons induced by the cavity field. Since both the absorption and dispersion of PTS are known to be intensity dependent, it appears that the bistability discovered in the present work belongs to a mixed type of dispersion and absorption. As we have found in our numerical analysis, when I_{in} increases from zero and reaches a point where n_{ς} can have three different values, the largest n_{ς} always satisfies the relation $\Delta - \lambda_{ps} = 0$. Further increase of I_{in} beyond that point leads to an increase of the refractive index of PTS. This may be understood in the following way. As the input intensity increases beyond a certain level, the number of virtual excitons becomes large enough that the lattice relaxation is

sufficiently high for the refractive index to deviate from the cavity resonance. Consequently, the cavity field switches to the lower branch. The dispersion effect plays a crucial role in this type of optical bistability.

As concluding remarks, we note that the virtual excitons and lattice vibrations in PTS indeed damp much faster than the damping in an ordinary cavity. This enables us to eliminate the excitonic and phononic variables adiabatically for the special kind of bistability discussed above. Furthermore, the novel phenomenonon of optical tristability is found by considering only a single phonon mode in PTS. It is therefore expected to find optical multistability if more phonon modes are included.

Acknowledgments

We gratefully acknowledge the Air Force Office of Scientific Research (AFSC), under Contract F49620-86-C-0009, and the Office of Naval Research for support of this research. The United States Government is authorized to reproduce and distribute reprints for governmental purposes notwithstanding any copyright notation hereon.


References

- 1. A. Mysyrowicz, D. Hulin, A. Antonetti, A. Migns, W. T. Masselink and H. Morkoc, Phys. Rev. Lett. <u>56</u>, 2748 (1986).
- 2. S. Schmitt-Rink and D. S. Chemla, Phys. Rev. Lett. <u>57</u>, 2752 (1986).
- 3. A. Von Lehmen, D. S. Chemla, J. E. Zucker and J. P. Heritage, Opt. Lett. 11, 609 (1986).
- 4. D. S. Chemla D. A. B. Miller and S. Schmitt-Rink, in <u>Optical Nonlinearities and Instabilities in Semiconductors</u>, ed. by H. Haug (Academic, New York, 1988), p. 83 ff.
- 5. B. I. Greene, J. Orenstein, R. R. Millard and L. R. Williams, Chem. Phys. Lett. <u>139</u>, 381 (1987); Phys. Rev. Lett. <u>58</u>, 2750 (1987).
- 6. B. I. Greene, J. F. Mueller, J. Orenstein, D. H. Rapkine, S. Schmitt-Rink and M. Thakur, Phys. Rev. Lett. <u>61</u>, 325 (1988).
- 7. G. J. Blanchard, J. P. Herítage, A. C. Von Lehmen, G. L. Baker and S. Etemad, Bull. Am. Phys. Soc. <u>34</u>, 452 (1989); Phys. Rev. Lett. <u>63</u>, 887 (1989).
- 8. X. S. Li, D. L. Lin, T. F. George and X. Sun, Phys. Rev. B, in press (#BE4168 15 Dec 89).
- 9. M. Reid, K. J. McNeil and D. F. Walls, Phys. Rev. A 24, 2029 (1981).
- 10. P. D. Townsend, G. L. Baker, N. E. Schlotter and S. Etemad, Synth. Met. 28, D633 (1989).
- 11. M. Thakur, Y. Shani, G. C. Chi and K. O'Brian, Synth. Met. <u>28</u>, D595 (1989).
- 12. See D. N. Batchelder, in <u>Polydiacetylenes</u>, ed. by D. Bloor and R. R. Chance (Martinus Nijhoff, Dordrecht, The Netherlands, 1985), p. 187 ff.
- 13. H. M. Gibbs, Optical Bistability: Controlling Light with Light (Academic, Orlando, 1985), Chap. 2.

Figure Caption

1. Intensity of the cavity field I versus the input field intensity I in. (a) $\Delta = \omega_{\rm ph} = 5.16$, ${\rm g}^2/\kappa = 0.1$; (b) $\Delta = \omega_{\rm ph}$, ${\rm g}^2/\kappa = 0.5$; (c) $\Delta = \omega_{\rm ph}$, ${\rm g}^2/\kappa = 1.0$; (d) $\Delta = \omega_{\rm ph}$, ${\rm g}^2/\kappa = 1.5$; (e) $\Delta = \omega_{\rm ph}$, ${\rm g}^2/\kappa = 2.0$; (f) $\Delta = 3.0$, ${\rm g}^2/\kappa = 1.0$. The dashed lines in (b) and (c) are hypothetical to complete the reversed hysteresis loop.

Fig. 1



01/1113/86/2

TECHNICAL REPORT DISTRIBUTION LIST, GEN

	No. Copies		No. Copies
Office of Naval Research Attn: Code 1113 800 N. Quincy Street Arlington, Virginia 22217-5000	2	Dr. David Young Code 334 NORDA NSTL, Mississippi 39529	1
Dr. Bernard Douda Naval Weapons Support Center Code 50C Crane, Indiana 47522-5050	1	Naval Weapons Center Attn: Dr. Ron Atkins Chemistry Division China Lake, California 93555	1
Naval Civil Engineering Laboratory Attn: Dr. R. W. Drisko, Code L52 Port Hueneme, California 93401	1	Scientific Advisor Commandant of the Marine Corps Code RD-1 Washington, D.C. 20380	1
Defense Technical Information Center Building 5, Cameron Station Alexandria, Virginia 22314	12 high quality	U.S. Army Research Office Attn: CRD-AA-IP P.O. Box 12211 Research Triangle Park, NC 27709	1
DTNSRDC Attn: Dr. H. Singerman Applied Chemistry Division Annapolis, Maryland 21401	1	Mr. John Boyle Materials Branch Naval Ship Engineering Center Philadelphia, Pennsylvania 19112	1
Dr. William Tolles Superintendent Chemistry Division, Code 6100 Naval Research Laboratory	1	Naval Ocean Systems Center Attn: Dr. S. Yamamoto Marine Sciences Division San Diego, California 91232	1
Washington, D.C. 20375-5000		Dr. David L. Nelson Chemistry Division Office of Naval Research 800 North Quincy Street Arlington, Virginia 22217	1

Dr. J. E. Jensen Hughes Research Laboratory 3011 Malibu Canyon Road Malibu, California 90265

Dr. J. H. Weaver
Department of Chemical Engineering
and Materials Science
University of Minnesota
Minneapolis, Minnesota 55455

Dr. A. Reisman

Microelectronics Center of North Carolina Dr. D. DiLella
Research Triangle Park, North Carolina Chemistry Depa
27709 George Washing

Dr. M. Grunze Laboratory for Surface Science and Technology University of Maine Orono, Maine 04469

Dr. J. Butler Naval Research Laboratory Code 6115 Washington D.C. 20375-5000

Dr. L. Interante Chemistry Department Rensselaer Polytechnic Institute Troy, New York 12181

Or. Irvin Heard Chemistry and Physics Department Lincoln University Lincoln University, Pennsylvania 19352

Dr. K.J. Klaubunde Department of Chemistry Kansas State University Manhattan, Kansas 66506 Dr. C. B. Harris
Department of Chemistry
University of California
Berkeley, California 94720

Dr. F. Kutzler
Department of Chemistry
Box 5055
Tennessee Technological University
Cookesville, Tennessee 38501

Dr. D. DiLella Chemistry Department George Washington University Washington D.C. 20052

Dr. R. Reeves Chemistry Department Renssaeler Polytechnic Institute Troy, New York 12181

Dr. Steven M. George Stanford University Department of Chemistry Stanford, CA 94305

Dr. Mark Johnson Yale University Department of Chemistry New Haven, CT 06511-8118

Dr. W. Knauer Hughes Research Laboratory 3011 Malibu Canyon Road Malibu, California 90265

Or. G. A. Somorjai Department of Chemistry University of California Berkeley, California 94720

Dr. J. Murday Naval Research Laboratory Code 6170 Washington, D.C. 20375-5000

Dr. J. B. Hudson Materials Division Rensselaer Polytechnic Institute Troy, New York 12181

Dr. Theodore E. Madey Surface Chemistry Section Department of Commerce National Bureau of Standards Washington, D.C. 20234

Or. J. E. Demuth
IBM Corporation
Thomas J. Watson Research Center
P.O. Box 218
Yorktown Heights, New York 10598

Dr. M. G. Lagally
Department of Metallurgical
and Mining Engineering
University of Wisconsin
Madison, Wisconsin 53706

Dr. R. P. Van Duyne Chemistry Department Northwestern University Evanston, Illinois 60637

Or. J. M. White Department of Chemistry University of Texas Austin, Texas 78712

Dr. D. E. Harrison Department of Physics Naval Postgraduate School Monterey, California 93940 Dr. R. L. Park
Director, Center of Materials
Research
University of Maryland
College Park, Maryland 20742

Dr. W. T. Peria Electrical Engineering Department University of Minnesota Minneapolis, Minnesota 55455

Dr. Keith H. Johnson
Department of Metallurgy and
Materials Science
Massachusetts Institute of Technology
Cambridge, Massachusetts 02139

Dr. S. Sibener Department of Chemistry James Franck Institute 5640 Ellis Avenue Chicago, Illinois 60637

Dr. Amold Green Quantum Surface Dynamics Branch Code 3817 Naval Weapons Center China Lake, California 93555

Dr. A. Wold Department of Chemistry Brown University Providence, Rhode Island 02912

Dr. S. L. Bernasek Department of Chemistry Princeton University Princeton, New Jersey 08544

Dr. W. Kohn
Department of Physics
University of California, San Diego
La Jolla, California 92037

Dr. F. Carter Code 6170 Naval Research Laboratory Washington, D.C. 20375-5000

Dr. Richard Colton Code 6170 Naval Research Laboratory Washington, D.C. 20375-5000

Dr. Dan Pierce National Bureau of Standards Optical Physics Division Washington, D.C. 20234

Dr. R. Stanley Williams
Department of Chemistry
University of California
Los Angeles, California 90024

Dr. R. P. Messmer Materials Characterization Lab. General Electric Company Schenectady, New York 22217

Dr. Robert Gomer Department of Chemistry James Franck Institute 5640 Ellis Avenue Chicago, Illinois 60637

Dr. Ronald Lee R301 Naval Surface Weapons Center White Oak Silver Spring, Maryland 20910

Dr. Paul Schoen Code 6190 Naval Research Laboratory Washington, D.C. 20375-5000 Dr. John T. Yates Department of Chemistry University of Pittsburgh Pittsburgh, Pennsylvania 15260

Dr. Richard Greene Code 5230 Naval Research Laboratory Washington, D.C. 20375-5000

Or. L. Kesmodel
Department of Physics
Indiana University
Bloomington, Indiana 47403

Dr. K. C. Janda University of Pittsburg Chemistry Building Pittsburg, PA 15260

Dr. E. A. Irene Department of Chemistry University of North Carolina Chapel Hill, North Carolina 27514

Dr. Adam Heller Bell Laboratories Murray Hill. New Jersey 07974

Dr. Martin Fleischmann Department of Chemistry University of Southampton Southampton 509 5NH UNITED KINGDOM

Dr. H. Tachikawa Chemistry Department Jackson State University Jackson, Mississippi 39217

Dr. John W. Wilkins Cornell University Laboratory of Atomic and Solid State Physics Ithaca, New York 14853

Dr. R. G. Wallis Department of Physics University of California Irvine, California 92664

Dr. D. Ramaker Chemistry Department George Washington University Washington, D.C. 20052

Dr. J. C. Hemminger Chemistry Department University of California Irvine, California 92717

Dr. T. F. George Chemistry Department University of Rochester Rochester, New York 14627

Or. G. Rubloff
IBM
Thomas J. Watson Research Center
P.O. Box 218
Yorktown Heights, New York 10598

Or. Horia Metiu Chemistry Department University of California Santa Barbara, California 93106

Dr. W. Goddard
Department of Chemistry and Chemical
Engineering
California Institute of Technology
Pasadena, California 91125

Dr. P. Hansma Department of Physics University of California Santa Barbara, California 93106

Dr. J. Baldeschwieler
Department of Chemistry and
Chemical Engineering
California Institute of Technology
Pasadena, California 91125

Dr. J. T. Keiser Department of Chemistry University of Richmond Richmond, Virginia 23173

Dr. R. W. Plummer Department of Physics University of Pennsylvania Philadelphia, Pennsylvania 19104

Dr. E. Yeager Department of Chemistry Case Western Reserve University Cleveland, Ohio 41106

Dr. N. Winograd
Department of Chemistry
Pennsylvania State University
University Park, Pennsylvania 16802

Dr. Roald Hoffmann Department of Chemistry Cornell University Ithaca, New York 14853

Dr. A. Steckl
Department of Electrical and
 Systems Engineering
Rensselaer Polytechnic Institute
Troy, NewYork 12181

Dr. G.H. Morrison Department of Chemistry Cornell University Ithaca, New York 14853